

Order Form

Featured System - Contour



Contact Details

Company _____

Contact Name _____

Delivery Address _____

Postcode _____

Tel No. _____

Fax No. _____

Order No. _____ Order Ref. _____

Date Required _____ Order Date _____

Customer Signature _____

Secured by Design Specification



Yes No

Colour Options

Standard White Brilliant White

Mahogany Mahogany on White

Golden Oak Golden Oak on White

Rosewood Rosewood on White

Dimensions/Orientation

X = slider O = fixed

VIEWED FROM OUTSIDE

Please indicate position of sliding sash (for 2 pane)

--	--

Direction of travel of sliding sash (3 pane).

O	X	O
---	---	---

Orientation for sashes in 4 pane doors is fixed as shown. (other variants on request)

O	X	X	O
---	---	---	---

Sliding sash Internal External

Overall width _____ mm

Overall height INCLUDING cills/add-ons _____ mm

Cill required CONFIRM Yes No

85mm (stub) 150mm 180mm

15mm frame extension to head to sides

30mm frame extension to head to sides

Low threshold 39mm (Weathered)

Low threshold 28mm (Unweathered - internal use only)

Mechanical outer frame

Mobility wheelchair access threshold and ramps Yes No

Silver Gold

Hardware Options

Shootbolt on lock (into head) Yes No

White Handle Gold Handle Chrome Handle

Black Handle Satin Silver Handle

Internal Locking Only Blanking Plate External

White L'Box Gold L'Box Chrome L'Box

Black L'Box Satin Silver L'Box

Aluminium Threshold Cover Silver Gold

Rain deflector (fitted to head) Yes No

Keyed Alike Cylinders Thumb Turn Cylinders

Midrail

Midrail position _____ mm (min 400m)

If midrail is **not** required in all sashes, indicate position on slider drawing opposite.

Drainage and Ventilation

Frame drainage None Concealed

Vented through frame head 4000mm² 8000mm²

Vented through 30mm extension 4000mm² 8000mm²

Standard positions for trickle vents are central (for single vents), or centrally over sashes (for two vents).

Special Instructions