

Order Guide

Veka Vertical Sliding Sash Windows

Options and advice for using the Sliders (UK) vertical sliding window order form.

Quotations – Please indicate if your enquiry is for price only by ticking the quotation box.

Contact / Address Details – Please complete accurately and in full ensuring that you provide a contact name in case we need to contact you.

Order Number and Reference – Please provide an order number at the top of the form and a reference for each window above the specification.

Delivery Date – Our standard lead time is 2-3 weeks please specify the date your windows are required by.

Dimensions – Height and width dimensions should be the overall dimensions including any extensions.

Conformity – Windows in the same room / elevation should be ordered together in order for us to match specification.

SUPERIOR SPECIFICATION AS STANDARD

Veka Profiles

- Fully sculptured sashes
- Outer frame depth 136mm
- Top sash height (small) 50mm
- Bottom sash height (large) 64mm
- Integral cill depth 155mm

Hardware

- Key locking sash locks (2No.over 800mm width).
- Ring pull to top sash.
- Hook sash lift to bottom (2No.over 800mm width).
- Tilt mechanism to both sashes for easy cleaning.
- Bespoke glazing packers for trouble free glazing.
- Opening restrictors for optional additional safety.

Glazing

- C Rated
- B Rated
- A Rated

ADDITIONAL OPTIONS

Veka profiles

- Decorative Horns Plant on horns fitted to the top sash.
- True Horns End milled engineered 'true' horns for stunning aesthetic appeal.
- Deep Bottom Rail A 105mm deep bottom rail to mimic traditional sightlines.
- 15/30/45mm Add-ons A comprehensive range of frame extensions.
- Fixing Brackets 175/200/250mm stainless steel fixing brackets.
- Snap-on Head Drip A 'Snap-on' weather bar for rain deflection.

Hardware

- Colour White, gold, chrome or satin chrome suited hardware.
- Restrictors Safety feature - sash travel restrictors to limit the sash opening.
- Trickle Vents 2000 or 4000mm² trickle vents can be fitted in the top rail of the top sash or in the head of the frame.

Glazing

- Glass Toughened, laminated, obscure or argon filled options.
- Astragal Georgian Bars GeoFast™ surface mounted sculptured Georgian bars replicate the sash profiles. Please indicate design on the order form.
- Internal Georgian Bars 18-25mm internal Georgian bars.
- Spacer Bar Colour Silver as standard with gold, bronze and white options. For A & B rated, black or grey Swiss spacer.
- Diamond Lead Choice of one side or both.
- Obscure Pattern Refer to standard Pilkington patterns.

Other

- Transom drop Standard is equal split. If a different arrangement is required please indicate the dimension from the top of the frame to the centre of the meeting point of the sashes.

